



STANDARD FEATURES

- Totally-Enclosed, Fan Cooled (TEFC)
- Stainless Steel Nameplate
- 12 Leads 213 Frame and Above
- Design C
- 208-230/460V 60 Hz
- Oversize Bearings
- 1.25 SF up to 100 HP, 1.15 Over 100 HP
- VPI and Additional Dip and Bake
- Cast Iron J Box, Rolled Steel Fan Cover
- Regreasable Bearings 254 Frame and Larger
- Sealed Bearings 215 Frame and Smaller
- Interchangeable C-Face
- Inverter Duty 10-1VT, 4-1CT
- Shaft Slings on Both Ends

- Gasketed J Box to Frame and Cover
- Double Drilled Feet
- CSA-C and US
- Class F Insulation
- Conduit Box Rotatable at 90° Stops

OPTIONS & MODIFICATIONS

- C-Face
- Resistance Thermal Detectors (RTD)
- Vibration Monitoring
- Heaters
- Specially Machined Shafts
- F-2 Assembly
- Bearing Isolators
- Special Paint Request

HP	FRAME	RPM	EPACT P/N	EPACT EFF	WEIGHT**	PREMIUM P/N	PREMIUM EFF	WEIGHT**
1	143T	1800	EET0014	82.5	46 lbs	EPT0014	85.5	52 lbs
	145T	1200	EET0016*					
1.5	143T	3600	EET00152	82.5	46 lbs			
	145T	1800	EET00154	84	59 lbs	EPT00154	86.5	56 lbs
2	182T	1200	EET00156*					
	145T	3600	EET0022	84	48 lbs			
3	145T	1800	EET0024	84	54 lbs	EPT0024	86.5	58 lbs
	184T	1200	EET0026	85.5	98 lbs			
5	182T	3600	EET0032*					
	182T	1800	EET0034	87.5	100 lbs	EPT0034 (C)	89.5	102 lbs
7.5	213T	1200	EET0036*					
	184T	3600	EET0052 (C)	87.5	110 lbs	EPT0052 (C)	88.5	116 lbs
10	184T	1800	EET0054 (C)	87.5	112 lbs	EPT0054 (C)	89.5	118 lbs
	215T	1200	EET0056*					
15	213T	3600	EET00752 (C)	88.5	148 lbs	EPT00752 (C)	89.5	158 lbs
	213T	1800	EET00754 (C)	89.5	148 lbs	EPT00754 (C)	91.7	162 lbs
20	254T	1200	EET00756*					
	215T	3600	EET0102 (C)	90.2	164 lbs	EPT0102 (C)	90.2	173 lbs
25	215T	1800	EET0104 (C)	89.5	172 lbs	EPT0104 (C)	91.7	180 lbs
	256T	1200	EET0106*					
30	254T	3600	EET0152 (C)	90.2	288 lbs	EPT0152 (C)	91	304 lbs
	254T	1800	EET0154 (C)	91	293 lbs	EPT0154 (C)	92.4	310 lbs
40	284T	1200	EET0156*					
	256T	3600	EET0202 (C)	90.2	335 lbs	EPT0202 (C)	91	334 lbs
50	256T	1800	EET0204 (C)	91	324 lbs	EPT0204 (C)	93	334 lbs
	286T	1200	EET0206	90.2	392 lbs			
60	284TS	3600	EET0252 (C)	91	386 lbs	EPT0252 (C)	91.7	406 lbs
	284T	1800	EET0254 (C)	92.4	394 lbs	EPT0254 (C)	93.6	414 lbs
75	324T	1200	EET0256	91.7	520 lbs			
	286TS	3600	EET0302 (C)	91	410 lbs	EPT0302 (C)	91.7	432 lbs
100	286T	1800	EET0304 (C)	92.4	411 lbs	EPT0304 (C)	93.6	438 lbs
	326T	1200	EET0306	91.7	552 lbs			
125	324TS	3600	EET0402 (C)	91.7	542 lbs	EPT0402 (C)	92.4	544 lbs
	324T	1800	EET0404 (C)	93	554 lbs	EPT0404 (C)	94.1	552 lbs
150	364T	1200	EET0406	93	718 lbs			
	326TS	3600	EET0502 (C)	92.4	565 lbs	EPT0502 (C)	93	584 lbs
200	326T	1800	EET0504 (C)	93	592 lbs	EPT0504 (C)	94.5	630 lbs
	365T	1200	EET0506*					
250	364TS	3600	EET0602 (C)	93	752 lbs	EPT0602 (C)	93.6	758 lbs
	364T	1800	EET0604 (C)	93.6	784 lbs	EPT0604 (C)	95	818 lbs
300	404T	1200	EET0606*					
	365TS	3600	EET0752 (C)	93	820 lbs	EPT0752 (C)	93.6	812 lbs
350	365T	1800	EET0754 (C)	94.1	810 lbs	EPT0754 (C)	95.4	838 lbs
	405T	1200	EET0756*					
400	405TS	3600	EET1002	93.6	1098 lbs	EPT1002	94.1	1090 lbs
	405T	1800	EET1004	94.5	1104 lbs	EPT1004	95.4	1110 lbs
450	444T	1200	EET1006*					
	444TS	3600	EET1252*			EPT1252*		
500	444T	1800	EET1254	94.5	1418 lbs	EPT1254	95.4	1408 lbs
	445T	1200	EET1236*					
550	445TS	3600	EET1502	94.5	1665 lbs	EPT1502*		
	445T	1800	EET1504	95	1734 lbs	EPT1504	95.8	1726 lbs
600	447T	1200	EET1506*					
	447TS	3600	EET2002	95	1840 lbs	EPT2002*		
650	447T	1800	EET2004	95	1840 lbs	EPT2004	96.2	1814 lbs
	449T	1200	EET2006*					

Part Numbers with (C) have C-face installation option; please specify when ordering

* Motor sizes available by special order only

**Shipping Weights

All Specifications are Subject to Change Without Notice